



20851 Johnson Street Unit #105, Pembroke Pines, FL 33029 - P: 305-883-9949 - - www.sumoilcorp.com

MIN-68

Mineral Oil Refrigeration Compressor Lubricant

MIN-68 is made from premium base stocks and offers optimized solubility in CFC, HCFC and blended refrigerants. MIN-68 offers exceptional chemical and thermal stability, and it provides a very long service life.

ATTRIBUTES

- Optimized solubility in CFC, HCFC and blended refrigerants
- Excellent coolant properties
- Carbon and varnish control to help reduce deposits
- Long oil life
- Controls rust for enhanced component protection
- High flash and auto-ignition points for added safety
- Good film strength and anti-wear properties
- Non-toxic/non-hazardous

TYPICAL LUBRICANT PROPERTIES

MIN-68 Grades	32	46	68	100
SUS Viscosity Grade	150	200	300	500
Viscosity cSt @ 40°C	30.5	49	66.8	110
Viscosity cSt @ 100°C	5.25	7.1	8.8	12.8
Flash Point °F (°C)	425 (218)	441 (227)	471 (244)	498 (259)
Pour Point °F (°C)	-49 (-45)	-47 (-44)	-44 (-42)	-35 (-37)
Copper Corrosion, 24 Hr	1a	1a	1a	1a